



304798

LABEL IS TO BE HUNG AT FINAL ASSEMBLY. Clamp between Ceiling Ring and Trim Ring.



VELUX®		www.veluxusa.com www.velux.ca 1-800-88-VELUX	Remove only after final inspection Retain for your records
 National Fenestration Rating Council® CERTIFIED	VELUX® VEL-N-15-00008-00001 Model TGF or TMF, TDD, Acrylic or Polycarbonate Dome, Flex Tunnel, Dual-glazed acrylic diffuser Thermal Opening Area = 0.10 m ² Insulation at Ceiling Modèle TGF ou TMF, TDD, Acrylique ou Polycarbonate Dôme, Tunnel Flexible, Diffuseur Double en Acrylique, Zone d'ouverture thermique = 0,10 m ² Isolant au plafond		
	ENERGY PERFORMANCE RATINGS ÉVALUATION DU RENDEMENT ÉNERGÉTIQUE		
U-Factor Valeur-U 0.50 2.84 (U.S./I-P) (Metric/SI)	Solar Heat Gain Coefficient Coefficient de gain chaleur solaire 0.21		
ADDITIONAL PERFORMANCE RATINGS ÉVALUATION SUPPLÉMENTAIRE DU RENDEMENT			
Visible Transmittance Transmission Visible 0.16	Air Leakage Infiltration d' Air ≤0.3 ≤1.5 (U.S./I-P) (Metric/SI)		
<p>Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for product performance information</p> <p style="text-align: center;">www.nfrc.org</p> <hr/> <p>Selon le fabricant, ces cotes sont conformes aux procédures applicables du NFRC servant à établir le rendement global du produit. Les cotes NFRC sont établies selon les conditions environnementales et des dimensions de produit spécifiques. NFRC ne recommande aucun produits et ne garantie aucun produits dans leurs applications et recommandations d'installations. Consultez la littérature du manufacturier pour de l'information sur le rendement de tout autre produit.</p> <p style="text-align: center;">www.nfrc.org</p>			
		ENERGY STAR® Qualified In All 50 States	
Meets or Exceeds C.E.C. Air Infiltration Requirements			

304798

LABEL IS TO BE HUNG AT FINAL ASSEMBLY. Clamp between Ceiling Ring and Trim Ring.



VELUX®

www.veluxusa.com
www.velux.ca
1-800-88-VELUX

- REMOVE ONLY AFTER FINAL INSPECTION
- RETAIN FOR YOUR RECORDS

Florida Prod. Approval
6393

TDI Product Evaluation
SK-12

TDI Product Evaluation
SK-15

WINDOW & DOOR
MANUFACTURERS ASSOCIATION
WDMA
Hallmark Certified
www.wdma.com

TGF, TGR, TMF and TMR
VELUX® SUN TUNNEL™
Licensee: 426-H-705

Manufacturer Stipulates Conformance as indicated below

CONFORMS TO

RATING

AAMA/WDMA/CSA 101/I.S.2/A440-11

TDDCC-PG125
Size Tested: 559 mm
Positive (Download) DP = 14,364 Pa (300 psf)

AAMA/WDMA/CSA 101/I.S.2/A440-08

CW-PG95 – 559 MM – TDD
Positive (Download) DP = 9,576 Pa (200 psf)

CSA A440S1-09

DP: +9576 / -4549 Pa (+200 / -95 psf)
Water Test Pressure = 720 Pa (15 psf)
Canadian Air Infiltration/Exfiltration = Fixed

The below only applies to product codes ending with 1000 and 1000E0

ASTM E-1996-05 /
ASTM E-1886-05

Cycle Pressure +50/-50
Wind Zone 3 Missile Level C