



National Fenestration Rating Council®

CERTIFIED

VELUX®

VEL-N-18-00028-00001

Skylight Model FS (10)
Tempered over Laminated Tempered
0.02 LoE3, Argon-filled IGU

Puits de lumière modèle FS (10),
Trempe sur laminé et trempé
0.02 LoE3, unité d'isolation de verre rempli d'argon

**ENERGY PERFORMANCE RATINGS
ÉVALUATION DU RENDEMENT ÉNERGÉTIQUE**

U-Factor Valeur-U	Solar Heat Gain Coefficient Coefficient de gain chaleur solaire
(U.S./I-P) 0.42	0.26
(Metric/SI) 2.38	

**ADDITIONAL PERFORMANCE RATINGS
ÉVALUATION SUPPLÉMENTAIRE DU RENDEMENT**

Visible Transmittance Transmission Visible 0.60	Air Leakage Infiltration d' Air -
	(U.S./I-P) (Metric/SI)

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for product performance information.

www.nfrc.org

Selon le fabricant, ces cotes sont conformes aux procédures applicables du NFRC servant à établir le rendement global du produit. Les cotes NFRC sont établies selon les conditions environnementales et des dimensions de produit spécifiques. NFRC ne recommande aucun produits et ne garantie aucun produits dans leurs applications et recommandations d'installations. Consultez la littérature du manufacturier pour de l'information sur le rendement de tout autre produit.

www.nfrc.org

**ENERGY STAR® Certified in Highlighted Regions
Certifié ENERGY STAR dans les régions en surbrillance**

Canada
energystar.gc.ca

U.S. / É.U.
energystar.gov

DO NOT REMOVE UNTIL FINAL INSPECTION. NE PAS RETIRER AVANT L'INSPECTION FINALE

Meets or Exceeds C.E.C. Air Infiltration Requirements

WINDOW & DOOR MANUFACTURERS ASSOCIATION
WDMA
Hallmark Certified
www.wdma.com

**VELUX Model
FS M08 2010**
Licensee: 426-H-672

Ratings for above size and smaller
Manufacturer Stipulates Conformance as indicated below

STANDARD	RATING
AAMA/WDMA/CSA 101/1.S.2/A440-11	SKG-PG100 Size Tested: 781 x 1397 mm (31 x 55 in) DP = 56498 Pa (1180 psf)
AAMA/WDMA/CSA 101/1.S.2/A440-08	Class CW-PG75 Size Tested: 781 x 1397 mm (31 x 55 in) DP = 30643 Pa (640 psf)
CSA A440S1-09	DP: +30643/-3591 Pa (+640/-75 psf) Water Test Pressure = 720 Pa (15 psf) Canadian Air Infiltration/Exfiltration = Fixed Level

**KEEP LABEL FOR
CODE INSPECTION
AND HOME RECORDS**

www.veluxusa.com
www.velux.ca
1-800-88-VELUX

VELUX America Inc.
PO Box 5001
Greenwood, SC 29648

VELUX®