

CCAN Aluminum Curb Sizing

| . | , | | • • • • • | | | . 2 |
|----------|------|-------------|---|-------------|-----|-----|
| | Size | Dimensions | | | | |
| Quantity | | Inside Curb | Outside Curb | Curb Height | | |
| | | | | 9" | 12" | 16" |
| | 2448 | 24"x48" | 27¾"x51¾" | | | |
| | 2496 | 24"x96" | 27¾"x99¾" | | | |
| | 2412 | 24"x120" | 27¾"x123¾" | | | |
| | 3636 | 36"x36" | 39¾"x39¾" | | | |
| | 3660 | 36"x60" | 39¾"x63¾" | | | |
| | 3672 | 36"x72" | 39¾"x75¾" | | | |
| | 3696 | 36"x96" | 39¾"x99¾" | | | |
| | 3612 | 36"x120" | 39¾"x123¾" | | | |
| | 4848 | 48"x48" | 51¾"x51¾" | | | |
| | 4860 | 48"x60" | 51¾"x63¾" | | | |
| | 4872 | 48"x72" | 51¾"x75¾" | | | |
| | 4896 | 48"x96" | 51¾"x99¾" | | | |
| | 4812 | 48"x120" | 51¾"x123¾" | | | |
| | 6060 | 60"x60" | 63 ³ / ₄ "x63 ³ / ₄ " | | | |
| | 6072 | 60"x72" | 63¾"x75¾" | | | |
| | 6096 | 60"x96" | 63 ³ / ₄ "x99 ³ / ₄ " | | | |
| <u> </u> | 6012 | 60"x120" | 63¾"x123¾" | | | |
| | 7272 | 72"x72" | 75¾"x75¾" | | | |

- 1. This drawing emphasizes the VELUX CCAN Aluminum Curb. This presentation illustrates a basic cross section for a VELUX CCAN Aluminum Curb utilized with a VELUX Commercial Dome installation in a 0-60 degree roof pitch application.
- 2. The architectural/structural design and specifications for the inclusion of a curb, such as the VELUX CCAN, in any roofing/ceiling application is determined and provided by others. The design criteria includes, but is not limited to design loads, structural configurations, structural framing member sizes and material, architectural finishes and integration with the roofing/ceiling systems of the building. VELUX recommends compliance by all designers and installers with all local and industry specific building codes and guidelines. VELUX assumes no responsibility or liability in the design, construction and performance of a building structure by others.



VELUX 1418 Evans Pond Road Greenwood, SC 29649 1-800-88-VELUX www.VELUXUSA.com

CCAN Aluminum Curb