



National Fenestration Rating Council®

CERTIFIED

**VELUX®**

**VEL-N-17-00032-00001**

**Skylight Model VS/VSE/VSS (04)  
Tempered over Laminated Heat-Strengthened  
0.02 LoE3, Argon-filled IGU**

**Puits de lumière modèle VS/VSE/VSS (04),  
Trempe sur laminé renforcit à la chaleur  
0.02 LoE3, unité d'isolation de verre rempli d'argon**

**ENERGY STAR® Certified in Highlighted Regions**  
**Certifié ENERGY STAR dans les régions en surbrillance**

**Canada**  
energystar.gc.ca

**U.S. / É.U.**  
energystar.gov

**ENERGY STAR**

**IAPMO ES #199**

TDI Product Evaluation  
SK-03  
Florida Prod. Approval  
13309

**ENERGY PERFORMANCE RATINGS**  
**ÉVALUATION DU RENDEMENT ÉNERGÉTIQUE**

**U-Factor**  
Valeur-U

(U.S./I-P)

**0.43**

(Metric/SI)

**2.44**

**Solar Heat Gain Coefficient**  
Coefficient de gain chaleur solaire

**0.23**

DO NOT REMOVE UNTIL FINAL INSPECTION/NE PAS RETIRER AVANT L'INSPECTION FINALE  
Meets or Exceeds C.E.C. Air Infiltration Requirements

WINDOW & DOOR  
MANUFACTURERS ASSOCIATION

**WDMA**

**Hallmark Certified**  
www.wdma.com

**VELUX Model**  
**VS M08 2004**  
Licensee: 426-H-670

Ratings for above size and smaller  
Manufacturer Stipulates Conformance as indicated below

**ADDITIONAL PERFORMANCE RATINGS**  
**ÉVALUATION SUPPLÉMENTAIRE DU RENDEMENT**

**Visible Transmittance**  
Transmission Visible

**0.53**

**Air Leakage**  
Infiltration d' Air

(U.S./I-P)

(Metric/SI)

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for product performance information.

www.nfrc.org

Selon le fabricant, ces cotes sont conformes aux procédures applicables du NFRC servant à établir le rendement global du produit. Les cotes NFRC sont établies selon les conditions environnementales et des dimensions de produit spécifiques. NFRC ne recommande aucun produits et ne garantie aucun produits dans leurs applications et recommandations d'installations. Consultez la littérature du manufacturier pour de l'information sur le rendement de tout autre produit.

www.nfrc.org

STANDARD	RATING
AAMA/WDMA/CSA 101/I.S.2/A440-11	SKG-PG105 Size Tested: 775 x 1390 mm (31 x 55 in) DP = 19152 Pa (440 psf)
AAMA/WDMA/CSA 101/I.S.2/A440-08	Class CW-PG80 Size Tested: 775 x 1390 mm (31 x 55 in) DP = 12950 Pa (270 psf)
CSA A440S1-09	DP: +12012/-3830 Pa (+270/-80 psf) Water Test Pressure = 720 Pa (15 psf) Canadian Air Infiltration/Exfiltration = A3 Level

17.6 mm Pane  
LA Research Report  
25885

**KEEP LABEL FOR  
CODE INSPECTION  
AND HOME RECORDS**

www.veluxusa.com  
www.velux.ca  
1-800-88-VELUX

VELUX America Inc.  
PO Box 5001  
Greenwood, SC 29648

**VELUX®**