



VELUX America Inc.
PO Box 5001
Greenwood, SC 29648-5001

864-941-5360 Phone
864-941-4870 Fax
www.veluxusa.com

Your reference

Our reference
V-USA-29-0

Date
April 14, 2011

RE: ESCAPE AND RESCUE ACCESS

To Whom It May Concern:

The VELUX Roof Window model GDL "Cabrio" meets the escape and rescue requirements as stated in the International Building Code (IBC) and the International Residential Code (IRC). The actual clear dimensions and other pertinent details of this model are indicated on the attached file, showing the actual sizes are well above the specified minimums.

Best Regards,

A handwritten signature in blue ink that reads "Roger T. LeBun".

Product Certification Engineer

Attachment
RLE/-



GDL Open Area:
 $(33.75" \times 40") / 144 = 9.38 \text{ ft}^2$

Roof Slope	X		H1		H2		C	
	mm	in.	mm	in.	mm	in.	mm	in.
35° - 39°	213	8.4	800	31.5	1146	45.1	1631	64.2
35° - 39°	263	10.4	850	33.5	1196	47.1	1681	66.2
35° - 39°	313	12.3	900	35.4	1246	49.1	1731	68.1
35° - 39°	363	14.3	950	37.4	1296	51.0	1781	70.1
35° - 39°	413	16.3	1000	39.4	1346	53.0	1831	72.1
35° - 39°	463	18.2	1050	41.3	1396	55.0	1881	74.1
35° - 39°	513	20.2	1100	43.3	1446	56.9	1931	76.0
40° - 42°	157	6.2	800	31.5	1090	42.9	1753	69.0
40° - 42°	207	8.1	850	33.5	1140	44.9	1803	71.0
40° - 42°	257	10.1	900	35.4	1190	46.9	1853	73.0
40° - 42°	307	12.1	950	37.4	1240	48.8	1903	74.9
40° - 42°	357	14.1	1000	39.4	1290	50.8	1953	76.9
40° - 42°	407	16.0	1050	41.3	1340	52.8	2003	78.9
40° - 42°	457	18.0	1100	43.3	1390	54.7	2053	80.8
43° - 45°	125	4.9	800	31.5	1058	41.7	1823	71.8
43° - 45°	175	6.9	850	33.5	1108	43.6	1873	73.7
43° - 45°	225	8.9	900	35.4	1158	45.6	1923	75.7
43° - 45°	275	10.8	950	37.4	1208	47.6	1973	77.7
43° - 45°	325	12.8	1000	39.4	1258	49.5	2023	79.6
43° - 45°	375	14.8	1050	41.3	1308	51.5	2073	81.6
43° - 45°	425	16.7	1100	43.3	1358	53.5	2123	83.6
46° - 48°	95	3.7	800	31.5	1028	40.5	1889	74.4
46° - 48°	145	5.7	850	33.5	1078	42.4	1939	76.3
46° - 48°	195	7.7	900	35.4	1128	44.4	1989	78.3
46° - 48°	245	9.6	950	37.4	1178	46.4	2039	80.3
46° - 48°	295	11.6	1000	39.4	1228	48.3	2089	82.2
46° - 48°	345	13.6	1050	41.3	1278	50.3	2139	84.2
46° - 48°	395	15.6	1100	43.3	1328	52.3	2189	86.2
49° - 53°	67	2.6	800	31.5	1000	39.4	1953	76.9
49° - 53°	117	4.6	850	33.5	1050	41.3	2003	78.9
49° - 53°	167	6.6	900	35.4	1100	43.3	2053	80.8
49° - 53°	217	8.5	950	37.4	1150	45.3	2103	82.8
49° - 53°	267	10.5	1000	39.4	1200	47.2	2153	84.8
49° - 53°	317	12.5	1050	41.3	1250	49.2	2203	86.7
49° - 53°	367	14.4	1100	43.3	1300	51.2	2253	88.7

