



National Fenestration Rating Council®

CERTIFIED

VELUX®

VEL-N-21-00032-00002

Skylight Model VCM/VCE/VCS (10)
Tempered over Laminated Tempered
0.02 LoE3, Argon-filled IGU

Puits de lumière modèle VCM/VCE/VCS (10),
Trempe sur laminé et trempe
0.02 LoE3, unité d'isolation de verre rempli d'argon

ENERGY PERFORMANCE RATINGS
ÉVALUATION DU RENDEMENT ÉNERGÉTIQUE

U-Factor
Valeur-U

(U.S./I-P) **0.49**
(Metric/SI) **2.78**

Solar Heat Gain Coefficient
Coefficient de gain chaleur solaire

0.24

ADDITIONAL PERFORMANCE RATINGS
ÉVALUATION SUPPLÉMENTAIRE DU RENDEMENT

Visible Transmittance
Transmission Visible

0.55

Air Leakage
Infiltration d' Air

(U.S./I-P) **-** (Metric/SI)

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for product performance information.

www.nfrc.org

Selon le fabricant, ces cotes sont conformes aux procédures applicables du NFRC servant à établir le rendement global du produit. Les cotes NFRC sont établies selon les conditions environnementales et des dimensions de produit spécifiques. NFRC ne recommande aucun produits et ne garantie aucun produits dans leurs applications et recommandations d'installations. Consultez la littérature du fabricant pour de l'information sur le rendement de tout autre produit.

www.nfrc.org


ENERGY STAR® Certified in Highlighted Regions
Certifié ENERGY STAR dans les régions en surbrillance

Canada
energystar.gc.ca



ENERGY STAR

U.S. / É.U.
energystar.gov



DO NOT REMOVE UNTIL FINAL INSPECTION NE PAS RETIRER AVANT L'INSPECTION FINALE

Meets or Exceeds C.E.C. Air Infiltration Requirements

WINDOW & DOOR
MANUFACTURERS ASSOCIATION
WDMA
Hallmark Certified
www.wdma.com

VELUX Model
VCM 4646 2010
Licensee: 426-H-695

Ratings for above size and smaller
Manufacturer Stipulates Conformance as indicated below

STANDARD

RATING

AAMA/WDMA/CSA
101/I.S.2/A440-11

SKG-PG40
Size Tested: 1305 x 1305 mm (51 x 51 in)
DP = 29686 Pa (620 psf)

AAMA/WDMA/CSA
101/I.S.2/A440-08

Class CW-PG30
Size Tested: 1305 x 1305 mm (51 x 51 in)
DP = 17237 Pa (360 psf)

CSA A440S1-09

DP: +17,237/-1430 Pa (+360/-30 psf)
Water Test Pressure = 720 Pa (15 psf)
Canadian Air Infiltration/Exfiltration = A3 Level

KEEP LABEL FOR
CODE INSPECTION
AND HOME RECORDS

www.veluxusa.com
www.velux.ca
1-800-88-VELUX

VELUX America Inc.
PO Box 5001
Greenwood, SC 29648

VELUX®