



TEST REPORT

Report No.: F8966.02-109-44

Rendered to:

VELUX America LLC
Greenwood, South Carolina

PRODUCT TYPE: Skylight

SERIES/MODEL: Dynamic Single Dome Skylight Polycarbonate Smooth (6' x 6') (0.150 thickness)

SPECIFICATION(S): Occupational Safety and Health Administration/U.S. Department of Labor Regulations (Standards- 29 CFR) - 1910.23(e) (8)

California Code of Regulations, Title 8, Section 3212

Test Date(s): 09/07/16

Report Date: 01/09/18

Test Record Retention Date: 09/07/20

- 1.0 Report Issued To:** VELUX America LLC
1418 Evans Pond Road
P.O. Box 5001
Greenwood, South Carolina 29648-5001
- 2.0 Test Laboratory:** Architectural Testing, Inc., an Intertek company ("Intertek-ATI")
130 Derry Court
York, Pennsylvania 17406-8405
717-764-7700

3.0 Project Summary:

- 3.1 Product Type:** Skylight
- 3.2 Series/Model:** Dynamic Single Dome Skylight Polycarbonate Smooth (6' x 6') (0.150 thickness)
- 3.3 Compliance Statement:** Results obtained are tested values and were secured by using test method(s) intended to address the designated performance specifications.
- 3.4 Test Date(s):** 09/07/16
- 3.5 Test Record Retention End Date:** All test records for this report will be retained until September 7, 2020.
- 3.6 Test Location:** Intertek-ATI test facility in York, Pennsylvania.
- 3.7 Test Specimen Source:** The test specimen(s) was provided by the client. Representative samples of the test specimen(s) will be retained by Intertek-ATI for a minimum of two years from the test completion date.
- 3.8 Drawing Reference:** The test specimen drawings have been reviewed by Intertek-ATI and are representative of the test specimen(s) reported herein. Test specimen construction was verified by Intertek-ATI per the drawings located in Appendix B. Any deviations are documented herein or on the drawings.

3.9 List of Official Observers:

<u>Name</u>	<u>Company</u>
Timothy J. McGill	Intertek-ATI
Joel Chronister	Intertek-ATI

4.0 Test Method (intended to address listed specification(s)):

Occupational Safety and Health Administration/U.S. Department of Labor Regulations (Standards- 29 CFR) - 1910.23(e) (8)

California Code of Regulations, Title 8, Section 3212

A 400 lb. weight, fabricated from a bag filled with lead shot, was placed on the center of the dome for a minimum of 60 seconds. The bag was removed and the test unit was inspected for any signs of damage or failure.

Additional Loading:

The specimen was taken to failure using sandbags placed on the center of the dome for a minimum of 60 seconds. The highest load causing penetration or damage was recorded.

5.0 Evaluation Scope:

Intertek Building & Construction (B&C) was contracted by VELUX America LLC, 1418 Evans Pond Road on December 4, 2017 to evaluate the OSHA fall protection testing to the most recent referenced document. Occupational Safety and Health Administration (OSHA)/U.S. Department of Labor Regulations Standard 29 CFR §1910.29 – Fall protection systems and falling object protection-criteria and practices. Section 1910.29(e)(1) requires a cover to be capable of supporting without failure at least twice the maximum intended load that may be imposed on the cover at any one time.

Intertek Building & Construction (B&C) was contracted by VELUX America LLC, 1418 Evans Pond Road on December 4, 2017 to evaluate the Cal/OSHA fall protection testing to the most recent referenced document. California Code of Regulations, Title 8, Section 3212 §(b), which states, "covers shall be capable of safely supporting the greater of 400 lbs or twice the weight of the employees, equipment and materials that may be imposed on any one square foot area of the cover at any time."

6.0 Test Specimen Description:

6.1 Product Sizes:

Overall Area: 42.1 ft ²	Width (inches)	Height (inches)
Overall size	77-7/8	77-7/8

6.2 Frame Construction:

Frame Member	Material	Description
Inner frame	Aluminum	Extruded
Dome clamp cover	Aluminum	Extruded

	Joinery Type	Detail
All corners	Mitered	Miter cut and welded

6.3 Reinforcement: No reinforcement was utilized

6.4 Weatherstripping:

Description	Quantity	Location
Custom-shaped gasket	1 row	Located around the interior perimeter of the inner frame
Gasket wick	1 per corner	Located at each mitered corner of the custom-shaped gasket

6.0 Test Specimen Description: (Continued)

6.5 Glazing: *No conclusions of any kind regarding the adequacy or inadequacy of the poly smooth in any glazed test specimen(s) can be made.*

Glazing Type	Glazing Method
5/32" poly smooth	The glazing was set from the exterior onto a custom-shaped gasket against the extruded aluminum frame. The glazing was secured using an aluminum extruded dome clamp cover with a bead of sealant on the glazing. The dome clamp cover was secured using spring clips and #10 x 5/8" self-tapping screws located 2" from all corners and 12" on center.

Location	Quantity	Daylight Opening (inches)	Glazing Bite (inches)
Dome	1	72-1/2 x 72-1/2	7/8

7.0 Installation: The specimen was installed into a Spruce-Pine-Fir wood buck.

Location	Anchor Description	Anchor Location
Aluminum frame	#10 x 1-1/2" pan head screw	8-1/2" from corners, 12" on center

8.0 Test Results: The results are tabulated as follows:

8.1 California (and OSHA) minimum loading:

Test Load	Load Location	Results
400 lbf	Center of dome	No visible damage

Note: The 400 lbf weight was gently applied perpendicular to the center of the dome. After 60 seconds of rest time, there was no visible damage to the glazing.

8.2 Additional loading (applied on the same unit in the listed order):

Test Load	Load Location	Results
501 lbf at rest	Center of dome	No visible damage
604 lbf at rest	Center of dome	No visible damage
706 lbf at rest	Center of dome	No visible damage
807 lbf at rest	Center of dome	No visible damage
909 lbf at rest	Center of dome	No visible damage
1009 lbf at rest	Center of dome	No visible damage
1112 lbf at rest	Center of dome	No visible damage
1215 lbf at rest	Center of dome	Corner welds cracked
1317 lbf at rest	Center of dome	No visible damage
1418 lbf at rest	Center of dome	No visible damage
1520 lbf at rest	Center of dome	No visible damage
1622 lbf at rest	Center of dome	Deglazing around corners
1723 lbf at rest	Center of dome	See Note #1

Note #1: At 1723 lbf, the load created on opening larger than one square foot.

9.0 Conclusion:

The specimen was evaluated in accordance with Occupational Safety and Health Administration (OSHA)/U.S. Department of Labor Regulations Standard 29 CFR §1910.29(e)(1) to be capable of supporting twice the maximum intended load, up to (760) ft-lb.

The specimen was evaluated in accordance with California Code of Regulations, Title 8, Section 3212 §(b) to be capable of safely supporting loads exceeding 400 ft-lb.

Intertek-ATI will service this report for the entire test record retention period. Test records such as detailed drawings, datasheets, representative samples of test specimens, or other pertinent project documentation, will be retained by Intertek-ATI for the entire test record retention period.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. It is the exclusive property of the client so named herein and relates only to the specimen(s) tested. This report may not be reproduced, except in full, without the written approval of Intertek-ATI.

For ARCHITECTURAL TESTING, Inc.

Joel Chronister
Technician

Timothy J. McGill
Manager – Product Testing

JC:asm/abo

Attachments (pages): This report is complete only when all attachments listed are included.

Appendix-A: Photograph(s) (1)

Appendix-B: Drawing(s) (16)

Appendix A
Photograph(s)



Photo No. 1
View of Tested Specimen






Photo No. 2
View of Tested Specimen

Appendix B

Drawing(s)


Report #: F8966.01-109-18
Date: 09/08/16
Verified by: *Jul Chernick*



HORIZONTAL CROSS-SECTION Sizes for CMA retrofits
 (TYPICAL FOR FRAME VERTICAL CROSS-SECTION)

PART SCHEDULE									
ITEM	QTY.	PART	PART NO.	DESCRIPTION	DRAWING NO.				COMMENTS
					Category	Commodity No.	Operation	Edition	
A	1	Dynamic exterior dome	_____	Polycarbonate, or acrylic, or impact modified acrylic	21	3036150A03	2	02	Thermoformed exterior dome
C	4	Inner frame	302359	6063/T5 Aluminum Powder coat color: NCS S 7500-N (Grey)	21	3023590000	00	01	Profile
					21	3023590A03	1	02	Cutting and punching
					21	3023590A03	9	02	Powder coat
					21	3023590A04	2	02	Welding
N/A	N/A	Primer	N/A	Clamp cover, Inner Frame, & Domes	21	3023590A05	2	01	Primer placement
D	4	Dome clamp cover	302360	6063/T5 Aluminum Powder coat color: NCS S 7500-N (Grey)	21	3023610000	00	01	Profile
					21	3023610A03	1	02	Cutting and drilling
					21	3023610A03	9	02	Powder coat
					21	3023600A04	2	01	Welding
E	N/A	Commercial sealant	305660	Silicone for commercial application	21	3036600A05	2	02	Silicone placement
F	4	High profile gasket	303612	TPE Color: Black	21	3036120000	00	01	Profile
					21	3036110000	3	01	Gasket groove cutting
					21	3036110A03	1	01	Gasket cutting
					21	3036110A04	2	02	Gasket welding
H*	4	Gasket wick	305659	Polyethylene felt for wicking	21	3056590000	00	02	Profile/cutting
					21	3056590A05	2	02	Wick placement
I	#	Spring clip	306222	301 Spring Temper Stainless Steel	21	3062220000	00	01	
					21	3062220A05	2	02	Spring clip placement

FASTENER SCHEDULE									
ITEM	QTY.	PART	PART NO.	DESCRIPTION	DRAWING NO.				COMMENTS
					Category	Commodity No.	Operation	Edition	
J	#	Torx screw	306225	Torx Pan head, SST, #2 drill point #10-16x5/8"	21	3062250000	00	01	Commodity drawing

GENERAL NOTES


- * Not Visible in this drawing
- 1. Unless noted otherwise, all parts listed are for CD1, CE1, CT1, CG1, CH1, CJ1 Commercial Dome skylights.
- 2. A copy of this drawing plus any other supplemental documentation regarding this skylight model will be maintained at the Skylight Technical Database in the following category location - Technical Data/Submittal Data/
- 3. Horizontal and Vertical Frame Cross-Section part sizes, materials and assembly are identical.
- 4. #8 or larger stainless steel installation fasteners, appropriate for supporting structure. Provided by others. One fastener per hole of Inner frame.
- 5. The CDx skylight installs directly on site built or prefabricated curbs, provided by others.

Size	Throat dimension mm	Product dimension mm
2'	717	758
3'	1022	1063
4'	1326.5	1368
5'	1631.5	1672.5
6'	1936	1977.5
7'	2241	2282
8'	2546	2857
10'	3155.5	3197
225	743	784
305	946	987
345	1047.5	1088.5
465	1352.5	1393.5

VELUX America Inc.
CONFIDENTIAL

THIS DRAWING IS THE SOLE PROPERTY OF VELUX AMERICA INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VELUX AMERICA IS PROHIBITED.


DIMENSIONS ARE IN MM
 GENERAL TOLERANCES:
 ANGULAR: ±1
 ONE PLACE DECIMAL: ±0.5


NOTE:

 SKY-GPM
 1418 Evans Pond Road PO Box 5001
 Greenwood, South Carolina 29648-5001

MATERIAL: Commercial Single Dome Skylight
 SPECIFICATION: CD1, CE1, CT1, CC1, CH1, CJ1
 FINISH: Product Certification
 SPECIFICATION: Typical Arrangement with Product List of Parts

STANDARDS: SIZE COMMODITY NO. REV. SCALE: OKD/DRAWN/DATE RLE/04/06/2016 SHEET 1 OF 1
 B 21.CD1CE1.0A0.63|01 1:1


Edition	Description of change	Date
02	Added note	3/29/16


 Report #: F8966.01-109-18
 Date: 09/08/16
 Verified by: *Joh. Christensen*






Flange straightness to ± 3.5 mm.
(Over 5' length)

Flange straightness to $-3.5 / + 9$ mm.
(Over 8' length)




Flange flatness to ± 3.5 mm.




SECTION A-A

VELUX America Inc.
CONFIDENTIAL



Rib detail for 2' & 3' width

Section B-B



Rib detail for 4', 5' & 6' width

Size	L	W	H (Exterior dome)	H (Second dome)	H (Third dome)	L1
2'	667.5	667.5	182	156.5	131	486
3'	972	972	276	250.5	225	638
4'	1277	1277	368	342.5	317	486
5'	1582	1582	467	441.5	416	638
6'	1886.5	1886.5	555.5	530	504.5	790.5
7'	2191	-	-	-	-	-
8'	2496	-	-	-	-	-
10'	3106	-	-	-	-	-


Note: 1. 4'x8' dome shown
2. Height is based on the width dimension

Material			
Polycarbonate, or acrylic, or impact modified acrylic			
VELUX		SKY-PRS	
450 Old Brickyard Rd., Greenwood, South Carolina 29648			
Approvals			
TMA-A			
Checked by/drawn by/date			
/MM/29.03.2016			
Scale	Unspec. meas.	General tolerance	Size
1:15	mm	±2	B

Specifications - generally				
Polycarbonate/Acrylic Alloy	309079.64			
Impact modified acrylic (Outer dome)	309209.64			
Impact modified acrylic (Inner dome)	309210.64			
Acrylic sheets for commercial	309052.64			
CDx,CEx				
Dome				
Product instructions no.				
Category	21	303615	0A0	32
Operation	32	02	02	02

Intertek |  Report #: F8966.01-109-18
 Date: 09/08/16
 Verified by: *Jul Chernits*

Edition	Description of change	Date







VELUX America Inc.
CONFIDENTIAL

Material				Specifications - generally				
6063/T5 Aluminum				Extruded Aluminum-Generally		309078.64		
VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648				<u>CDx, CEx, CTx, CGx, CHx, CJx</u>				
Approvals TMA-A				Inner frame Profile				
Checked by/drawn by/date /MM/20.01.2016				Product instructions no.				
Scale 2:1	Unspec. meas. mm	General tolerance ±0.5	Size B	Category 21	302359	000	00	01

Report #: F8966.01-109-18
 Date: 09/08/16
 Verified by: *Jed Chernick*

Edition	Description of change	Date
02	Added CG2 sizes	3/22/16



Size	L	Number of holes
2 foot	757	2
3 foot	1062	3
4 foot	1366	4
5 foot	1671	5
6 foot	1976	6
7 foot	2281	7
8 foot	2586	8
10 foot	3195	10
225	719	2
305	922	3
345	1024	3
465	1329	4

VELUX America Inc.
CONFIDENTIAL

VELUX SKY-PRS
 450 Old Brickyard Rd., Greenwood, South Carolina 29648

CDx,CEx,CTx,CGx,CHx,CJx

Inner frame
 Cutting and punching

Checked by/drawn by/date
 /REC/21.03.2016


Product instructions no.
302359

Scale	Unspec. meas.	General tolerance	Size	Category	Operation	Edition
1:1	mm	±1	C	21	0A0	31 02


Edition	Description of change	Date
02	Added view "Detail D"	3/28/16


 Report #: F8966.01-109-18
 Date: 09/08/16
 Verified by: *Jul Chernits*


Size	L
2'	716
3'	1021
4'	1326
5'	1630
6'	1935
7'	2240
8'	2545
10'	3155
225	678
305	881
345	983
465	1288





SECTION A-A




Fully weld along outer profile
 Note: Max weld height allowed is 1.5mm




DETAIL C
 SCALE 2 : 5



DETAIL B
 SCALE 1 : 2



DETAIL D
 SCALE 2 : 1




VELUX America Inc.
CONFIDENTIAL

VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648				CDx, CEx, CTx, CGx, CHx, CJx			
Approvals				Dome inner frame Welding			
Checked by/drawn by/date /RC/28.03.2016				Product instructions no.			
Scale 1:5	Unspec. meas. mm	General tolerance ±2	Size B	Category 21	302359	0A0	42
				Operation	42	Edition	02

	Report #:	F8966.01-109-18
	Date:	09/08/16
	Verified by:	<i>Jul Chernits</i>

Edition	Description of change	Date



VELUX America Inc.
CONFIDENTIAL


----- = Primered areas

Notes:
1. Primer should be dry to tacky before installation.
2. Prime using only approved silicone primer.


VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648				<u>CDx, CEx, CTx, CHx, CGx, Cjx</u>				
Approvals				Clamp cover, Inner Frame, & Domes Primer Placement				
Checked by/drawn by/date /MM/29.03.2016				Product instructions no.				
Scale 1:1	Unspec. meas. mm	General tolerance ±	Size	Category 21	302359	0A0	Operation 52	Edition 01


 Report #: F8966.01-109-18
 Date: 09/08/16
 Verified by: *Jed Chernick*

Edition	Description of change	Date



**VELUX America Inc.
CONFIDENTIAL**





DETAIL A
SCALE 5 : 1

- Notes:
1. Cross sectional area- 138 mm sq.
 2. Break Corners- .38R
 3. Purchased lineal length is 120"



Material				Specifications - generally						
6063/T5 Aluminum				Extruded Aluminum-Generally		309078.64				
VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648				<u>CDx, CEx, CTx, CHx, CGx, CJx</u>						
Approvals TMA-A				Dome clamp cover Profile						
Checked by/drawn by/date /MM/21.03.2016				Product instructions no.						
Scale 2:1	Unspec. meas. mm	General tolerance ±.5	Size A	Category 21	302361	000	00	01	Operation	Edition

Intertek Report #: F8966.01-109-18
 Date: 09/08/16
 Verified by: *Jed Chernick*

Edition	Description of change	Date
02	Added CG2 sizes	3/22/16



SECTION A-A



4.1 mm diameter

**VELUX America Inc.
CONFIDENTIAL**

Size	L
2 foot	709
3 foot	1014
4 foot	1318
5 foot	1623
6 foot	1928
7 foot	2233
8 foot	2538
10 foot	3147
225	671
305	874
345	976
465	1281



Note: 1. Cutting drawing is for both the dome clamp cover and the tall dome clamp cover.
 2. Pre drilled 4mm hole goes through both legs of clamp cover.

VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648		CDx, CEx, CTx, CHx, CGx, CJx	
Approvals		Dome clamp cover Cutting and drilling	
Checked by/drawn by/date /RC/22.03.2016		Product instructions no.	
Scale 1:1	Unspec. meas. mm	General tolerance ±.5	Size B
Category 21	302361	0A0	31 02


 Report #: F8966.01-109-18
 Date: 09/08/16
 Verified by: *Jul Chernick*

Edition	Description of change	Date

Size	L
2'	709
3'	1014
4'	1319
5'	1623
6'	1928
7'	2233
8'	2538
10'	3148
225	734
305	937
345	1039
465	1344



Scale 1:1


VELUX America Inc.
CONFIDENTIAL

Note: welding drawing is for both the dome clamp cover and the tall dome clamp cover

VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648				CDx, CEx, CTx, CHx, CGx, CJx			
Approvals				Dome clamp cover welding drawing			
Checked by/drawn by/date /MM/20.01.2016				Product instructions no.			
Scale	Unspec. meas.	General tolerance	Size	Category		Operation	Edition
1:2	mm	±2	B	21	302360	0A0 42	01

	Report #:	F8966.01-109-18
	Date:	09/08/16
	Verified by:	<i>Jul Chernits</i>

Edition	Description of change	Date
02	Added note	3/29/16



Notes:
 Silicone bead shape is not important.
 Min/Max diameter is used to determine total area.
 No gaps in silicone allowed.
 No squeeze out allowed on lens.

VELUX America Inc.
CONFIDENTIAL

VELUX SKY-PRS
 450 Old Brickyard Rd., Greenwood, South Carolina 29648

Approvals			
Checked by/drawn by/date /MM/29.03.2016			
Scale 2:1	Unspec. meas. mm	General tolerance ±1	Size A


Specifications - generally				
Silicone for commercial application		309213.64		
<u>CDx, CEx, CTx, CHx, CGx, CJx</u>				
Clamp Frame Silicone placement				
Product instructions no.				
Category	21	303660	0A0	52 02

Edition	Description of change	Date

	Report #:	F8966.01-109-18
	Date:	09/08/16
	Verified by:	<i>Jed Chumick</i>


Measure	Tol.
< 2.5	0.35
2.5-4	0.4
4-6.3	0.5
6.3-10	0.7
10-16	0.8
16-54	1

Angles $\pm 1^\circ$




VELUX America Inc.
CONFIDENTIAL

- Notes:
- Cross sectional area- 300.7 mm sq.
 - Purchased lineal length is 120"



Scale 1:1

- 103-50D
- 64A




Material				Specifications - generally				
TPE Color: Black				TPE for Gaskets 309034.64				
VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648				CDx,CEx,CTx,CGx,CHx,CJx				
Approvals TMA-A				High profile gasket				
Checked by/drawn by/date /MM/25.01.2016				Product instructions no.				
Scale 4:1	Unspec. meas. mm	General tolerance See chart	Size B	Category 21	303612	000	00	01

Edition	Description of change	Date




Snip corner as shown

	Report #:	F8966.01-109-18
	Date:	09/08/16
	Verified by:	<i>Jul Chernits</i>



DETAIL A
SCALE 1 : 2

Max 1mm flashing allowed in this area



SECTION B-B
SCALE 1 : 1

Depth of condensation groove
Max. 9
Min. 8


VELUX America Inc.
CONFIDENTIAL

VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648				CDx,CEx,CTx,CGx,CHx,CJx Gasket groove cutting					
Approvals				Product instructions no.					
Checked by/drawn by/date /MM/20.01.2016				Category	21	303611	000	39	01
Scale	Unspec. meas.	General tolerance	Size						
1:20	mm	±0.5	B						


 Report #: F8966.01-109-18
 Date: 09/08/16
 Verified by: *Jul Cherniob*


Edition	Description of change	Date
02	Corrected 1/2 sizes L & L2 dimensions	3/29/16

Size	L	L2
2'	659	713
3'	964	1017
4'	1268	1322
5'	1573	1627
6'	1878	1932
7'	2183	2237
8'	2488	2541
10'	3097	3151
225	621	675
305	824	878
345	926	980
465	1231	1285




SECTION A-A

Max. surface deviation in this area after welding 1mm typ.



Max. 2mm flashing allowed in this area

Max. 1mm flashing allowed in this area



Max. 1mm flashing allowed in this area


All other areas 3mm flashing allowed

VELUX America Inc.
CONFIDENTIAL

VELUX		SKY-PRS		CDx, CEx, CTx, CGx, CHx, CJx	
450 Old Brickyard Rd., Greenwood, South Carolina 29648		Gasket welding		Product instructions no.	
Checked by/drawn by/date /RC/29.03.2016		Category		21	
Scale 1:2	Unspec. meas. mm	General tolerance ±2	Size B	303611	0A0
This drawing must not be copied, published or used in any other way without permission		VELUX A/S reg. office: Ådalsvej 99, DK-2970 Hørsholm. CVR-no. 30003519		42	02

	Report #:	F8966.01-109-18
	Date:	09/08/16
	Verified by:	<i>Jul Chernick</i>

Edition	Description of change	Date
02	Revised material description	3/29/16




VELUX America Inc.
CONFIDENTIAL


Material				Specifications - generally											
Wool felt for wicking (grey)				Foam gasket wick mat'l commercial domes		309212.64									
VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648				<u>CDx, CEx, CTx, CGx, CHx, CJx</u>											
Approvals TMA-B				Gasket wick											
Checked by/drawn by/date /MM/29.03.2016				Profile/cutting											
Scale 2:1				Product instructions no.											
Unspec. meas. mm		General tolerance ±1		Size A		Category 21		305659		000		Operation 00		Edition 02	

	Report #:	F8966.01-109-18
	Date:	09/08/16
	Verified by:	<i>Jul Chernits</i>

Edition	Description of change	Date
02	Added note	3/29/16



Wick must not extend beyond this surface



Wick must contact all 4 posts

DETAIL A
SCALE 1 : 2


Place wicks in all four corners

VELUX America Inc.
CONFIDENTIAL

VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648				<u>CDx, CEx, CTx, CGx, CHx, CJx</u>			
Approvals				Gasket			
Checked by/drawn by/date /MM/29.03.2016				Wick placement			
Scale 1:10				Product instructions no.			
Unspec. meas. mm	General tolerance ±1	Size A	Category 21	305659	0A0	Operation 52	Edition 02

	Report #:	F8966.01-109-18
	Date:	09/08/16
	Verified by:	<i>Jul Chernis</i>

Edition	Description of change	Date



VELUX America Inc.
CONFIDENTIAL

Material				Specifications - generally			
Torx Pan head, SST, #2 drill point #10-16x5/8"				Stainless steel screws		414010.64	
VELUX SKY-PRS 450 Old Brickyard Rd., Greenwood, South Carolina 29648				<u>CDx, CEx, CTx, CGx, CHx, CJx</u>			
Approvals TMA-A				Torx screw			
Checked by/drawn by/date /MM/20.01.2016				Product instructions no.			
Scale 5:1	Unspec. meas. Inches	General tolerance ±.015	Size A	Category 21	306225	000	00 01